



Original post set 1820 by Hendricks with witnesses: 16' beech N 81 W 25 links, 25' dogwood S 29 E 35 links per Marion County Atlas pg. 10. Fatout 1-24-1881 called no stone nor witnesses per Perry Township Legal Survey Book pg. 71. Calculations show the corner to have been set by a Legal Survey per Perry Township Legal Survey Book, pg. 71, 1/2 way on line from the SW to the NW corner. We know today this was probably not the correct way to do this; but because it is recorded, it will remain 1/2 way on line. MCSO 10-2-64 called a cross with a brass bolt. Wilcoxen 6-4-93 called a brass bolt. Wilcoxen 9-7-95 called same. Excavated by Wilcoxen 6-13-98 and Harrison set in concrete.

HC543104

REF.	DISTANCE	DESCRIPTION	
1.	28.71′	Cut 'x' in median	
2.	68,29'	Rd N PwP#1-668 B 8'up	
3,	91.52′	Rd SE PwP#833-1021 36"up	
4.	99.36′	Top nut	
5.	147.27'	Rd S PwP#4403 30"up	
6.	34.63'	Cut 'x' N-rim manhole	
7.	30.54'	Due S to E Q 36-15-3 (Harrison)	
8.	75.12′	Cut 'x' in median	
9.	-76.70'	Cut 'x' hdwl	
10.	133.02'	Rd NE PwP#833-1020 10"up	
11.	195.52′	NE porch at foundation	